

# ATV950: For High performance Solid and Mechanical movement - IP55.







## ATV950 (IP54/55)

Protection against dust and water jet

Power range : 0.75 to 90kW Voltage Range: 380 to 480V

Overload capacity: ND: 110% for 60 sec HD: **150% for 60 sec** 

Communication: Modbus TCP & Ethernet IP-Dual port for redundant communication

Optional Communication: EtherCAT, Profinet, Profibus, etc.

r ronbus, etc.

IOs: 8 DI, 3 RO, 3 AI, 2 AO, ( standard)

#### Withstand Harsh environment

- •IP 54/55 Protection
- •3C3 & 3S3 coated
- •Ambient temperature is 50° C without deration
- •Graphical detachable keypad IP65

#### **Embedded application functions**

- Master/Slave with Multi Drive Link
- Backspin for Progressive Cavity Pump
- Backlash sequence
- Rope slack for cranes
- Break logic Control for hoisting
- Safety function card

## Energy efficiency:

- •Energy monitoring with accuracy >95%
- •Embedded energy dashboards periodic trends
- •Monitor energy consumption, detect the abnormality in poconsumption (too high/low)

## Future ready IIOT drive :


- •Remote monitoring -Webserver is embedded
- •Achilles certified against cyber threats
- •Ethernet embedded

#### Service oriented drive:

- •Real time data is available
- •5 maintenance scheduling events available
- •Diagnostic of IGBT on single click
- •Dynamic QR code troubleshooting

SIL3/PLe Certified VFD DC choke inbuilt (0.75 – 90kW)





V VV







**Altivar Process ATV900 catalog** 

# Targeted applications

### MMM:

Long Conveyor, Downhill Conveyor, Kiln, Pusher car, St stacker reclaimer, Hopper Gate Control, Skip Drive, Cranes, Lift, Roller Table, Crusher, Vibro feeders, etc with or without **Master Slave, AFE, asset management** 







## O&G:

Progressive Cavity Pump, Electrically Submersible Pump, with or without **Backspin control**, offshore rig, Onshore Extraction, Cranes, Pipeline control.

### **CPG**

Sugar crusher, Conveyor, Mixer, Centrifuge, Hot rotary dryers, Pulper, Winder-Unwinder, Mixer





